

TABLEAU COMPARATIF LAMINATEURS GRANDS FORMATS A FROID

| |  |  |  |  |  |  |  |  |
|---|---|---|---|--|---|---|---|---|
| | EM720 | EM880 | EM1180 | EM1180SH | EM1380 | EMS1380SH | EM1580 | EM1580SH |
| Référence produit: | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Largeur (m): | 0,720m | 0,880m | 1,180m | 1,180m | 1,380m | 1,380m | 1,580m | 1,580m |
| Contre-collage sur support adhésif: | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Plastification et adhésivage: | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Plastification 1 face: | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| 1 rouleau chauffant 50-60°C | | | | ✓ | | ✓ | | ✓ |
| Film de 25µ à 350µ: | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Utilisation de films. | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Epaisseur différente sur le recto/verso | | | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Pédale de commande: | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Stand (pieds): | Option | Option | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Dérouleur/Enrouleur | | | Option | Option | Option | Option | Option | Option |
| Vitesse: | 2m / mn | 2m / mn | 2m / mn | 3m / mn | 2m / mn | 3m / mn | 2m / mn | 3m / mn |
| Epaisseur Maximum pour le montage: | 15 mm | 15 mm | 12 mm | 25 mm | 25 mm | 25 mm | 25 mm | 25 mm |
| Consommation (W) | 50 W | 50 W | 70 W | 178 W | 70 W | 1310 W | 70 W | 1500 W |